


FUCHS Special Applications **CASSIDA**



Product Range
Food Grade
Lubricants

MOVING YOUR WORLD





FUCHS LUBRICANTS SOUTH AFRICA

We don't just develop lubricants for highly complex challenges in a wide range of industries, we develop innovative lubricant solutions that enable the mobility of tomorrow. Our goal: to keep our customers' world in motion. Efficient, sustainable, reliable. Today and tomorrow.

What can we move for you?

FUCHS LUBRICANTS SOUTH AFRICA

Facts and figures

Company: FUCHS LUBRICANTS SOUTH AFRICA A COMPANY OF THE FUCHS GROUP

Headquarters: Johannesburg, Gauteng

Product range: A full range of more than 2,000 products and 6,000 articles

Certifications: IATF 16949, ISO 14001, ISO 21469, ISO 45001, ISO 50001

Since 1931, we have been pursuing the same goal: to keep the world moving. With innovative and technological lubricant solutions that have a sustainable impact on the future. Unconditional reliability is our top priority, it is the foundation of our company and basis for everything that defines us.

Reliability is both a driver and a demand. And it's a promise to all our customers in the fields of automotive suppliers and OEMs, mechanical engineering, metal processing, mining and exploration, aerospace, energy, construction and transport, agriculture and forestry, as well as the paper, steel, metal, cement, forging and food industries, but also qualified lubricant dealers, car dealerships and workshops.

Long-term experience, high development strength and the fulfillment of far-reaching standards are the basis for the special quality of our world-leading product brands. We deliver solutions that are simply more efficient and therefore more sustainable. We always think in holistic solutions. For the development of individual solutions, we enter into an intensive customer dialog with you. This is the way we live up to our claim of moving your world.

MOVING YOUR WORLD





MOVING YOUR WORLD

by setting new standards in safe food lubrication solutions

The CASSIDA product line of FUCHS LUBRICANTS offers a comprehensive range of high-performance lubricants for the food and beverage industries, including fully synthetic as well as semi-synthetic and white-oil-based products. Each product's composition is always optimised to ensure maximum suitability for their respective application.

This product catalogue introduces our product portfolio and gives an overview of the wide range of CASSIDA products, including CASSIDA Fluids (fully synthetic), CASSIDA Greases (fully synthetic) and CASSIDA FM Lubricants (white-oil-based and semi-synthetic).

The food experts of the FUCHS LUBRICANTS team or your local sales partner will be happy to assist you in finding the best products for your application. You will receive individual, competent advice and recommendations for products that are best suited for fulfilling your particular requirements.





Contents

ABOUT CASSIDA

8–11

Industries Served	8
Highest Safety Standards	10

CASSIDA FLUIDS

12–21

FULLY SYNTHETIC PRODUCTS

Chain Oils	14
Compressor Fluids	15
Direct Contact Fluids - Multiple Applications	16
Gear Fluids	17
Hydraulic Oils	18
Vacuum Pump Fluids	18
Maintenance Fluids and Specialties	19

CASSIDA GREASES

22–29

FULLY SYNTHETIC PRODUCTS

Regular Load	24
Extreme Pressure	24
Heavy Duty	24
Specialties	25

CASSIDA FM RANGE

28–35

SEMI-SYNTHETIC AND WHITE-OIL-BASED PRODUCTS

Hydraulic Oils	30
Gear Oils	30
Specialties	31
Greases	34

Grease Gun	35
------------------	----

Industries Served by CASSIDA Food Grade Lubricants



Beverage and brewing industry

The production of food, beverages and related products puts the strictest requirements on the lubricants used in the manufacturing process. Consumer protection is absolutely essential. Incidental oil contamination during the bottling and canning process must be avoided by breweries and beverage manufacturers, who brew, mix, can and bottle millions of gallons of beverages for global markets every year.



Meat and poultry industry

Millions of pounds of meat and poultry are processed every year. Just as in all other food industries, the safety of the production process is crucial. CASSIDA food grade lubricants support this safety. In addition, ensuring that the production process runs smoothly and is highly effective (meaning longer component lifetimes and extended maintenance intervals) is our number one priority.



Dairy industry

Customers from the dairy industry as well as the other food-related industries benefit from the excellent quality of the CASSIDA portfolio, which has been confirmed by numerous OEM approvals given by well-known manufacturers of production and manufacturing equipment. This assures that the highest demands of the industry are met.



Bakery and confectionery industry

With the high temperatures required by the bakery and confectionery industry, high heat resistance and stability of the lubricant is crucial. FUCHS LUBRICANTS's research into extreme applications ensures that CASSIDA food grade lubricants perform at the highest level to allow for safe and reliable production and manufacturing processes.



Animal feed industry

Only safe feed will allow safe food to be produced. CASSIDA food grade lubricants provide this safety to the producers of animal feed. The products comply with the vast variety of feed requirements for livestock and other animals – from dairy cows and poultry to pets and fish.



Edible oil processing industry

In modern cuisine and with changing eating habits, edible oil, such as olive oil, sunflower oil and rapeseed oil, play an integral role in our diets. With CASSIDA food grade lubricants, FUCHS LUBRICANTS offers a wide choice of lubricating fluids and greases for safe and efficient lubrication of the production processes.

Serving the Highest Safety Standards of the Food and Beverage Industry

Our product portfolio – at a glance

Lubricants for the production, processing and packaging of food, beverages, medications and cosmetic products must fulfil stringent requirements. Consumer protection is crucial, which is why FUCHS LUBRICANTS practises the highest safety standards in all aspects of development, production, sales and after-sales service.

FUCHS LUBRICANTS customers benefit from the excellent quality of the CASSIDA product line, which has OEM approvals from well-known manufacturers of production and manufacturing equipment.

FUCHS LUBRICANTS food grade lubricants are formulated with the most advanced rust and oxidation, anti-wear and extreme-pressure additives available, all of which provide the maximum level of protection for your expensive food processing equipment. From hydraulic systems and transmissions to bearings and compressors: close cooperation already during the development phase pays off for our customers.

Safety, our number one priority

All lubricants for the production, processing and packaging of food, beverages, medications and cosmetic products must fulfil stringent requirements. Consumer protection is crucial, which is why food safety is very important in all aspects of development, production, sales and after-sales service. This is the reason why all of our food grade lubricants are registered by NSF International in accordance with the respective food-related categories.

Our manufacturing plant in Kaiserslautern as well as the food grade lubricants produced there are certified in accordance with the international standard ISO 21469. This standard determines the hygienic requirements for the composition, manufacturing and use of lubricants that may have incidental contact with food products – assuring that our products fulfil the highest possible safety standard.

Additionally, our CASSIDA products fulfil the strict requirements of both Jewish and Muslim laws and regulations. The respective Kosher and Halal certificates guarantee the highest possible level of product and food safety.

Our most important product: individual consulting and service

We set standards not only with our high-performance products, but also with our exceptional service! This includes providing advice on how to optimise the use of food grade lubricants taking into account stringent QA management procedures in order to avoid food contamination (in accordance with HACCP = Hazard Analysis and Critical Control Points), examination of used lubricants, development of lubrication and maintenance schedules, support in changing lubricants, active support for practical testing, careful documentation of all measures and much more.

Finding comprehensive, sustainable and safe solutions for all tribological issues arising from our customers' requirements and their applications is our declared goal. Customer seminars and training sessions held globally complete our service programme.

With its competent technical advice and widespread sales network, our global Food Division team supports you in your production and processing activities to ensure that you will always achieve optimal results.

NSF registered
ISO certified



Kosher certified



Halaal certified



Company Member



In Partnership with




Guide to Symbols



Roller bearings



Plain bearings



Flushing



High temperature



Low temperature



Can seamers and sterilisers



Chains



Conveyors



Gears – open



Gears – enclosed



Extreme pressure



Industrial coolants



Heat transfer



Hydraulics



Valves, taps and fittings




Compressors



Direct food contact



Sugar dissolving



Vacuum pumps



Maintenance spray



Slideways



Mounting/assembly/
disassembly aid



Maintenance aid



Worm gears



Linkages, pins



Anti-corrosive



NSF registered



CASSIDA FLUIDS

CASSIDA lubricating fluids based on fully synthetic base oils are developed to meet related industry specifications and to fulfil the stringent guidelines governing food-compatible lubricants. The high-performance lubricating fluids of the CASSIDA range enable the efficient operation of demanding manufacturing processes, a higher degree of utilisation of machines and a reduction in maintenance costs. They are used in various branches of the food and beverage industry.

FUCHS LUBRICANTS extensive range of food grade lubricating fluids offers the user a wide choice of CASSIDA-branded products for lifetime and total loss lubrication. In addition to mineral-oil-based fluids, a very diverse selection of synthetic lubricating fluids are available for a wide range of applications in the food and beverage industry.

These high-performance lubricating fluids enable the efficient operation of demanding production and manufacturing processes, a higher degree of utilisation of machines and a reduction in maintenance.


FUCHS LUBRICANTS researches constantly to increase performance and offer optimum lubricating fluids for maximum safety in food grade applications.

CASSIDA Fluids (fully synthetic)

Chain Oils	
CASSIDA CHAIN OIL 150 320 SPRAY 460 1500 1500 SPRAY 5000 SPRAY ..	14
CASSIDA CHAIN OIL LT LT SPRAY	14
CASSIDA CHAIN OIL SP	14
CASSIDA CHAIN OIL HTE	14
CASSIDA CHAIN OIL XTE	15
CASSIDA CHAIN OIL HTX	15
<hr/>	
Compressor Fluids	
CASSIDA FLUID CR 32 46 68 100 150	15
RENISO SYNTH 68	15
<hr/>	
Direct Contact Fluids - Multiple Applications	
CASSIDA FLUID DC 20 32	16
CASSIDA FLUID DCE 15 DCE 15 SPRAY	16
<hr/>	
Gear Fluids	
CASSIDA FLUID GL 150 220 320 460 680	17
CASSIDA FLUID GLE 150 220	17
CASSIDA FLUID WG 220 320 460 680 1000	17
<hr/>	
Hydraulic Oils	
CASSIDA FLUID HF 15 32 46 68 100	18
CASSIDA FLUID HFS 15 32 46 68 100	18
<hr/>	
Vacuum Pump Fluids	
CASSIDA FLUID VP 68 100	18
<hr/>	
Maintenance Fluids and Specialties	
CASSIDA FLUID FL 5 FL 5 SPRAY	19
CASSIDA SILICONE FLUID CASSIDA SILICONE FLUID SPRAY	19
CASSIDA PTFE DRY SPRAY	19
CASSIDA FLUID CP CASSIDA FLUID CP SPRAY	20
CASSIDA COOLANT	20

CHAIN OILS

CASSIDA CHAIN OIL | 150 | 320 Spray | 460 | 1500 | 1500 Spray | 5000 Spray


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA CHAIN OIL 150	150	19	-30 to +140 (upper peak: +150)	
CASSIDA CHAIN OIL 320 SPRAY	320*	34*	-40 to +140 (upper peak: +150)	
CASSIDA CHAIN OIL 460	460	43	-30 to +140 (upper peak: +150)	
CASSIDA CHAIN OIL 1500	1500	135	-30 to +140 (upper peak: +150)	
CASSIDA CHAIN OIL 1500 SPRAY	1500*	135*	-10 to +140 (upper peak: +150)	
CASSIDA CHAIN OIL 5000 SPRAY	5000*	350*	-10 to +100 (upper peak: +150)	

Fully synthetic, very high-performance chain oils. Highly resistant to fling-off or wash-off. Excellent protection against wear and corrosion.

Main application: Lubrication of drive and transport chains in the food industry. Can be applied by brush, via bath, automatic lubrication systems or spraying.

*after evaporation of solvent

CASSIDA CHAIN OIL LT | LT Spray


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA CHAIN OIL LT	32	6.5	-50 to +140 (lower peak: -60)	
CASSIDA CHAIN OIL LT SPRAY	32*	6.5*	-50 to +120 (lower peak: -60)	

Fully synthetic, high-performance anti-wear chain oil suitable for a wide range of temperatures, including sub-zero conditions.

Main application: Transport mechanisms inside food freezers such as spiral freezers. Lubrication of metal-metal and metal-ceramic contact points in open machinery, such as slideways and chains. Plain and anti-friction bearings.

*after evaporation of solvent

CASSIDA CHAIN OIL SP


	Viscosity at 40°C [mm ² /s]	Viscosity at 40°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA CHAIN OIL SP	85	460*	-30 to +140 (upper peak: +150)	

Fully synthetic, high-performance, anti-wear chain oil with excellent creeping and penetrating features.

Main application: Drive and transport chains in the food industry, slideways, levers, joints and bolts, ropes, spindles and guide pulleys. Also intended for use in equipment for manufacturing food packaging.

*after evaporation of solvent

CASSIDA CHAIN OIL HTE


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA CHAIN OIL HTE	220	20	-25 to +240	

Fully synthetic, ester-based, high-temperature chain lubricant suitable for temperatures of up to 240°C.


Main application: Drive and transport chains in the food industry. Also intended for use in equipment for manufacturing food packaging.

CHAIN OILS

CASSIDA CHAIN OIL XTE


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA CHAIN OIL XTE	194	18	-20 to +300	
Fully synthetic high-temperature chain lubricant with exceptional thermal stability.		Main application: Drive and transport chains in the food industry (e.g. bakeries). Also intended for use in equipment for manufacturing food packaging.		

CASSIDA CHAIN OIL HTX


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA CHAIN OIL HTX	330	40	-15 to >+300	
Fully synthetic, extreme-temperature chain lubricant suitable for temperatures up to more than 300°C.		Main application: Drive and transport chains in the food industry (e.g. bakeries). Also intended for use in equipment for manufacturing food packaging.		

COMPRESSOR FLUIDS

CASSIDA FLUID CR 32 | 46 | 68 | 100 | 150


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FLUID CR 32	32	6.1	-30 to +100 (upper peak: +120)	DIN 51506 VBL, VCL, VDL
CASSIDA FLUID CR 46	46	8.0	-30 to +100 (upper peak: +120)	DIN 51506 VBL, VCL, VDL
CASSIDA FLUID CR 68	68	11	-30 to +100 (upper peak: +120)	DIN 51506 VBL, VCL, VDL
CASSIDA FLUID CR 100	100	14	-30 to +100 (upper peak: +120)	DIN 51506 VBL, VCL, VDL
CASSIDA FLUID CR 150	150	19	-30 to +100 (upper peak: +120)	DIN 51506 VBL, VCL, VDL
Fully synthetic, very high-performance, long-life compressor oils. Meet DIN 51506 VBL, VCL, VDL and ISO 6743-3A DAH, DAG, DAJ specifications.		Main application: Oil-flooded rotary vane and screw air compressors in food processing plants.		

RENISO SYNTH 68

	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
RENISO SYNTH 68	68	10.50		DIN 51503-1, Category KAA
Fully synthetic lubricants for refrigeration compressors used in the food industry.		Main application: Recommended for use in piston as well as oil injected screw compressors for highly stressed ammonia applications and/or for deep evaporating temperatures. Can also be used in CO ₂ (R744) applications as a not miscible CO ₂ refrigeration oil.		

DIRECT CONTACT FLUIDS - MULTIPLE APPLICATIONS


CASSIDA FLUID DC 20 | 32

	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FLUID DC 20	23	4.8	-40 to +100	
CASSIDA FLUID DC 32	32	6	-40 to +100	

Fully synthetic, multipurpose, low-volatility fluids suitable for both direct and incidental food contact applications. Can handle a wide range of application temperatures and have excellent thermal and oxidative stability to minimise cracking and promote long service life.

Main application: In absorber oil columns designed to remove traces of hexane from steam/air/hexane mixtures. As forming oil for the manufacture of both two- and three-piece cans for the food and beverage industry. In closed circuit and pressureless heat transfer systems with a bulk oil temperature of approximately -30°C to 280°C where direct food contact may occur.

CASSIDA FLUID DCE 15 | CASSIDA FLUID DCE 15 Spray

	Viscosity at 20°C [mm ² /s]	Viscosity at 40°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FLUID DCE 15	31	14.8	-10 to +110 (upper peak: +120)	
CASSIDA FLUID DCE 15 SPRAY	31*	14.8*	-10 to +110 (upper peak: +120)	




Synthetic multifunctional mineral oil hydrocarbon free direct contact fluid for food processing applications in the food manufacturing industry.

Main application: Release agent used on grills, loaf pans, cutters, boning benches, chopping blocks or other hard surfaces to help prevent food from adhering during processing. Dough Divider lubrication and forming oil for the manufacture of both two and three piece cans for food and beverages (stamping, deep drawing and bending). Stamping and deep drawing of aluminium foils for food-packaging. Lubrication of lightly loaded chains.

*without propellant

GEAR FLUIDS





CASSIDA FLUID GL 150 | 220 | 320 | 460 | 680

  	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FLUID GL 150	150	19	-45 to +140 (upper peak: +150)	DIN 51517 CLP / DIN 51506 VBL, VCL
CASSIDA FLUID GL 220	220	25	-40 to +140 (upper peak: +150)	DIN 51517 CLP / DIN 51506 VBL
CASSIDA FLUID GL 320	320	33	-35 to +140 (upper peak: +150)	DIN 51517 CLP
CASSIDA FLUID GL 460	460	44	-35 to +140 (upper peak: +150)	DIN 51517 CLP
CASSIDA FLUID GL 680	680	59	-30 to +140 (upper peak: +150)	DIN 51517 CLP

Fully synthetic, very high-performance, long-life, anti-wear gear oils. Meet DIN 51517 CLP and ISO 6743/6 specifications.

Main application: Suitable for gearboxes on food handling and processing equipment. May also be used for general machine lubrication, for example, on chains.




CASSIDA FLUID GLE 150 | 220

   	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FLUID GLE 150	150	19	-40 to +140 (upper peak: +150)	DIN 51517 CLP
CASSIDA FLUID GLE 220	220	25	-40 to +140 (upper peak: +150)	DIN 51517 CLP

Fully synthetic, high-performance, anti-wear gear fluids for use in the food canning industry. Provides excellent lubrication, even when operating in locations where the product may be subject to contamination with water, juice and food. CASSIDA FLUID GLE holds these contaminants in suspension, thus protecting metal surfaces from wear and corrosion. Approved by Angelus Sanitary Can Seaming Company for can seamer lubrication.

Main application: Lubrication of rotary can seaming machines, including both enclosed and total loss systems, and for circulating and bearing oil systems where contamination with water or food juices can occur.

CASSIDA FLUID WG 220 | 320 | 460 | 680 | 1000


  	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FLUID WG 220	220	42	-35 to +160	DIN 51517 CLP
CASSIDA FLUID WG 320	320	61	-35 to +160	DIN 51517 CLP
CASSIDA FLUID WG 460	460	83	-30 to +160	DIN 51517 CLP
CASSIDA FLUID WG 680	680	122	-25 to +160	DIN 51517 CLP
CASSIDA FLUID WG 1000	1000	163	-25 to +160	DIN 51517 CLP

Fully synthetic, high-performance gear lubricants for worm gearboxes. High resistance to micro-pitting. Provides exceptional thermal stability and corrosion protection. Exceptional low-friction characteristics providing efficient power transmission. Meet DIN 51717 CLP and ISO 6743/6 specifications.

Main application: For the lubrication of worm gearboxes in food processing plants. Ideal for all worm gear applications. Suitable for use in situations where equipment gets routinely cleaned before and after use and where water might enter the lubricant.

HYDRAULIC OILS


CASSIDA FLUID HF 15 | 32 | 46 | 68 | 100

	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FLUID HF 15	15	3.6	-65 to +100 (upper peak: +120)	DIN 51524 HLP
CASSIDA FLUID HF 32	32	6	-60 to +140 (upper peak: +150)	DIN 51524 HLP, HVLP
CASSIDA FLUID HF 46	46	8	-59 to +140 (upper peak: +150)	DIN 51524 HLP, HVLP
CASSIDA FLUID HF 68	68	11	-52 to +140 (upper peak: +150)	DIN 51524 HLP, HVLP DIN 51517 CLP
CASSIDA FLUID HF 100	100	14	-45 to +140 (upper peak: +150)	DIN 51524 HLP, HVLP DIN 51517 CLP

Fully synthetic, high-performance, long-life, anti-wear hydraulic oils. Meet ISO 6743/4 HM, DIN 51524 HLP, HVLP and DIN 51517 CLP (ISO 68 and ISO 100) specifications.

Main application: Hydraulic systems, hydrostatic gears and control systems, plain and anti-friction bearings on food handling and processing equipment.

CASSIDA FLUID HFS 15 | 32 | 46 | 68 | 100


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FLUID HFS 15	15	4	-62 to +100 (upper peak: +120)	DIN 51524 HLP
CASSIDA FLUID HFS 32	32	6	-60 to +140 (upper peak: +150)	DIN 51524 HLP, HVLP DIN 51517 CLP
CASSIDA FLUID HFS 46	46	8	-60 to +140 (upper peak: +150)	DIN 51524 HLP, HVLP DIN 51517 CLP
CASSIDA FLUID HFS 68	68	11	-50 to +140 (upper peak: +150)	DIN 51524 HLP, HVLP DIN 51517 CLP
CASSIDA FLUID HFS 100	100	15	-45 to +140 (upper peak: +150)	DIN 51524 HLP, HVLP DIN 51517 CLP

Fully synthetic, high-performance, long-life, anti-wear hydraulic oils with boosted solvency and lubricity. Resist the formation of harmful oxidation products, even at elevated temperatures. Meet ISO 6743/4 HV and DIN 51524 HLP, HVLP and DIN 51517 CLP (HFS 68) specifications.

Main application: Hydraulic systems, hydrostatic gears and control systems, plain and anti-friction bearings on food handling and processing equipment. Can be used on demanding injection moulding machinery.

VACUUM PUMP FLUIDS

CASSIDA FLUID VP 68 | 100


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FLUID VP 68	68	10.5	-45 to +120 (upper peak: +140)	DIN 51506 VBL, VCL, VDL
CASSIDA FLUID VP 100	100	14	-40 to +120 (upper peak: +140)	DIN 51506 VBL, VCL, VDL

Fully synthetic, high-performance vacuum pump oils.

Main application: Vacuum pumps producing a medium vacuum, used in the food and beverage processing and packing industry.

MAINTENANCE FLUIDS and SPECIALTIES

CASSIDA FLUID FL 5 | FL 5 Spray


	Viscosity at 20°C [mm ² /s]	Viscosity at 40°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FLUID FL 5	3.8	1.1	n.a.	
CASSIDA FLUID FL 5 SPRAY	3.8*	1.1*	-60 to +110	

Fully synthetic penetrating fluid with excellent creeping and penetrating features. Capillary effect allows quick penetration between rusty and encrusted contact surfaces. Lubricates and protects against corrosion. Has a neutral odour and taste.

Main application: Penetrating fluid for use in food grade equipment. Can be used for the disassembling of screws, interlocking nuts and other components. Offers corrosion protection for metal components. Can be used for lubrication of various non-demanding applications where food grade lubricants are required.

*without propellant

CASSIDA SILICONE FLUID | CASSIDA SILICONE FLUID Spray


	Viscosity at 25°C [mm ² /s]	Viscosity at 40°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA SILICONE FLUID	350	270	-40 to +200 (upper peak: +220)	
CASSIDA SILICONE FLUID Spray	1000*	730*	-40 to +200 (upper peak: +220)	

Silicone-based, fully synthetic, multipurpose fluid. Thermal stability up to 250°C. Excellent adhesive properties minimise fling-off in use and wash-off by both cold and hot water. Readily displaces water. Formulated for use on metal-to-non-metal or non-metal-to-non-metal contact surfaces.

Main application: For lubrication of conveyors; slow rotating machinery; small, slow-speed bearings and pivot points found in equipment in the food industry.

*without propellant

CASSIDA PTFE DRY Spray

	Viscosity at 20°C [mm ² /s]	Temperature range [°C]
CASSIDA PTFE DRY SPRAY	0.8*	-50 to +270


Synthetic PTFE multipurpose and maintenance lubricant, based on a unique blend of components.

Main application: For use on belts, cams, chains, cables, conveyors, sliding tracks, joints, pivots, lifts, pulleys, threaded parts, bolts, rollers, taps, valves and many other moving parts. For lubrication and protection of seals and guides, operating in food, pharmaceutical and other clean environments where incidental food contact is possible.

*including solvent

MAINTENANCE FLUIDS and SPECIALTIES

CASSIDA FLUID CP | CASSIDA FLUID CP Spray

	Viscosity at 20°C [mm ² /s]	Viscosity at 40°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FLUID CP	4.9*	3.8*	n.a.	
CASSIDA FLUID CP SPRAY	4.9**	3.8**	-30 to +100	


Easy-to-handle, fully synthetic corrosion protection fluid with excellent yield for use in machinery in the food and beverage processing and packaging industry. Provides a thin, highly efficient molecular film on components.

Main application: Protection for machinery of all kind during shipping and distribution. For metal parts and tools after galvanic conditioning and cleaning processes. For gearbox housings, gear-wheels, couplings, driveshafts, measuring tools, precision tools, etc. As a temporary protection of sub-assemblies.

* including solvent

** without propellant, including solvent

CASSIDA COOLANT

	Viscosity at 20°C [mm ² /s]	Viscosity at 40°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA COOLANT	47	17	-45 to +120	

Propylene-glycol-based fluid containing anti-corrosion additives, for use in closed systems to chill, cool or heat food or beverages in food industry applications. Designed to be used in mixtures with potable water. Suitable for operation in the range of -45°C to 120°C.

Main application: Secondary cooling, or heating, in the food and beverage industry. For use in closed cooling systems, including those where there is potential for incidental food contact. Not to be used for applications where there is direct contact between food and the coolant.


CASSIDA GREASES

CASSIDA greases are fully based on synthetics and fulfil the same technical requirements as non-food grade lubricants – i.e. to reduce friction and wear or to protect against corrosion. For the food and beverage industry they support maximum food safety. With our range of CASSIDA greases, we cover all of the applications where there is potential for incidental food contact – as found in various branches of the food and beverage industry.

Included in the CASSIDA range of greases are direct contact lubricants which are both NSF H1 and also 3H registered for safety. This means the lubricants are acceptable for incidental contact with food as well as for use as release agents on hard surfaces which are in direct contact with meat and poultry.

Our CASSIDA GREASE EPS range of lubricants has been developed to provide high performance and wear protection for machinery operating at high pressures and loads. At slower speeds, high pressures and high loads, a heavy-duty grease is required which helps protect machinery. We provide CASSIDA greases that are specifically designed for heavy-loaded and shock-loaded applications.

Other product series include highly water-resistant greases, assembly pastes and low-temperature greases.



CASSIDA Greases

Regular Load

CASSIDA GREASE RLS 000 00 0 1 2	24
---	----

Extreme Pressure

CASSIDA GREASE EPS 00 1 2	24
-------------------------------------	----

Heavy Duty





CASSIDA GREASE HDS 00 2	24
---------------------------------	----

Specialties

CASSIDA GREASE GTS 2 GTS SPRAY	25
CASSIDA GREASE GTM 2	25
CASSIDA GREASE GTX 0 2	25
CASSIDA GREASE HTS 2	25
CASSIDA GREASE LTS 1	26
CASSIDA GREASE CLEAR 2	26
CASSIDA GREASE MD 2	26
CASSIDA GREASE FC 1 2	27
CASSIDA PASTE AP.....	27

REGULAR LOAD

CASSIDA GREASE RLS 000 | 00 | 0 | 1 | 2




	Thickener	Viscosity at 40°C [mm²/s]	Viscosity at 100°C [mm²/s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA GREASE RLS 000	AICx	100	13	-50 to +100 (upper peak: +120)	<000	
CASSIDA GREASE RLS 00	AICx	100	13	-45 to +100 (upper peak: +120)	00	
CASSIDA GREASE RLS 0	AICx	150	18	-40 to +100 (upper peak: +120)	0	
CASSIDA GREASE RLS 1	AICx	150	18	-40 to +120 (upper peak: +140)	1	
CASSIDA GREASE RLS 2	AICx	150	18	-35 to +120 (upper peak: +140)	2	

High-performance, regular-load aluminium complex greases with synthetic base fluid.

Main application: For use on bearings, bushings and linkages on food manufacturing equipment. CASSIDA GREASE RLS 0 and 00 are particularly recommended for centralised lube systems or other similar systems where an NLGI 2 grease may be difficult to dispense.

EXTREME PRESSURE

CASSIDA GREASE EPS 00 | 1 | 2



	Thickener	Viscosity at 40°C [mm²/s]	Viscosity at 100°C [mm²/s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA GREASE EPS 00	AICx	220	25	-45 to +100 (upper peak: +120)	00	
CASSIDA GREASE EPS 1	AICx	220	25	-40 to +120 (upper peak: +140)	1	
CASSIDA GREASE EPS 2	AICx	220	25	-35 to +120 (upper peak: +140)	2	

High-performance, extreme-pressure aluminium complex greases with synthetic base fluid.

Main application: For use on bearings, bushings and linkages on food manufacturing equipment, particularly where high pressure and loads, high temperatures and water spray occur. CASSIDA GREASE EPS 00 is especially recommended for centralised lube systems and enclosed gears.

HEAVY DUTY

CASSIDA GREASE HDS 00 | 2




	Thickener	Viscosity at 40°C [mm²/s]	Viscosity at 100°C [mm²/s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA GREASE HDS 00	AICX	800	68	-35 to +120 (upper peak: +120)	00	
CASSIDA GREASE HDS 2	AICX	800	68	-35 to +120 (upper peak: +140)	2	

High-performance, high-viscosity heavy-duty aluminium complex greases with synthetic base fluid.

Main application: For use on bearings, bushings and linkages on food manufacturing equipment, particularly where slower speeds, high pressure and loads, high temperatures and water spray are present. CASSIDA GREASE HDS 00 is recommended for open gears and centralised lube systems.

SPECIALTIES

CASSIDA GREASE GTS 2 | GTS SPRAY



	Thickener	Viscosity at 40°C [mm²/s]	Viscosity at 100°C [mm²/s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA GREASE GTS 2	CSX	85	12.8	-45 to +170 (upper peak: +200)	2	
CASSIDA GREASE GTS SPRAY	CSX	85	12.8**	-45 to +170 (upper peak: +200)	2*	

Speciality extreme-pressure calcium sulphonate complex greases with synthetic base fluid. Excellent extreme pressure, anti-wear and corrosion prevention properties.

Main application: For use on bearings of electric motors, pumps, conveyors, mixers, gear units and medium- to high-speed bearings operating up to 170°C.

**without propellant



CASSIDA GREASE GTM 2

	Thickener	Viscosity at 40°C [mm²/s]	Viscosity at 100°C [mm²/s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA GREASE GTM 2	CSX	220	25	-40 to +160	2	

Speciality synthetic extreme-pressure grease for food and beverage processing equipment.

Main application: For use on bearings of electric motors, pumps, conveyors, mixers and robotic applications.



CASSIDA GREASE GTX 0 | 2

	Thickener	Viscosity at 40°C [mm²/s]	Viscosity at 100°C [mm²/s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA GREASE GTX 0	CSX	460	44	-35 to +160 (upper peak: +200)	0	
CASSIDA GREASE GTX 2	CSX	460	44	-35 to +180 (upper peak: +220)	2	

High-performance, extreme-pressure calcium sulphonate complex grease with synthetic base fluid. Excellent extreme pressure, anti-wear and corrosion prevention properties.

Main application: For use on bearings of electric motors, pumps, conveyors, mixers, gear units and bearings. Heavy-loaded and shock-loaded applications with low- to medium-speed bearings operating up to 180°C, such as machines used to process pet food and animal feed.

CASSIDA GREASE HTS 2

	Thickener	Viscosity at 40°C [mm²/s]	Viscosity at 100°C [mm²/s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA GREASE HTS 2	Inorganic	400	40	-30 to +200 (upper peak: +220)	2	



Inorganically thickened grease with synthetic base fluid.

Main application: Suitable for applications on food manufacturing equipment where high temperatures (peak 220°C) may be experienced.



* Color Coding: For cartridges only

SPECIALTIES



CASSIDA GREASE LTS 1

	Thickener	Viscosity at 40°C [mm²/s]	Viscosity at 100°C [mm²/s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA GREASE LTS 1	AICx	20	4.5	-50 to +100 (upper peak: +110)	1	
High-performance aluminium complex grease with low-viscosity synthetic base fluid.		Main application: For use on bearings, bushing and linkages on food manufacturing equipment. Particularly recommended for use in cold storage situations with temperatures down to -50°C.				

CASSIDA GREASE CLEAR 2



	Thickener	Viscosity at 40°C [mm²/s]	Viscosity at 100°C [mm²/s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA GREASE CLEAR 2	Inorganic	75	11.5	-30 to +170	2	
Inorganically thickened clear grease with synthetic base fluid and highly micronised white solid lubricant (PTFE).		Main application: Lubrication of plain or roller bearings, joints, linkages and slides. Lubrication and protection of seals and guides, operating in food, pharmaceutical and other clean environments.				

CASSIDA GREASE MD 2

	Thickener	Viscosity at 40°C [mm²/s]	Viscosity at 100°C [mm²/s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA GREASE MD 2	PTFE	650	250	-40 to +200 (upper peak: +250)	2-3	
High-performance, silicone-based speciality grease specially developed for the lubrication and sealing of taps, valves and fittings with EPDM seals. Suitable for use with other seal materials normally used in food machinery lubrication systems. Good resistance to hot water, steam and disinfectant solutions.		Main application: Taps, flow meters and fittings used for the handling of water, drinks and beer. Seals on autoclaves and sterilisers. Suitable for continuous operation at temperatures up to 180°C and short-term exposure to temperatures not exceeding 250°C.				

SPECIALTIES


CASSIDA GREASE FC 1 | 2

	Thickener	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA GREASE FC 1	PTFE	510	47	-25 to +260 (upper peak: +280)	1	
CASSIDA GREASE FC 2	PTFE	510	47	-25 to +260 (upper peak: +280)	2	

Fully synthetic, high-performance, high-temperature greases for the filled-for-life lubrication of bearings and seals used in extreme temperatures and/or aggressive environments. Effective anti-corrosion prevention characteristics. Excellent elastomer compatibility. Suitable for applications where components might be exposed to reactive chemicals and gases; chemically inert or non-reactive in the event of contact with strong acids, alkalis and halogens. Excellent elastomer compatibility.

Main application: Plain/roller bearing elements, joints, microbearings, precision tools, linkages and mechanical seals. Suitable for continuous operation at temperatures up to 260°C and short-term exposure to temperatures not exceeding 300°C.

CASSIDA PASTE AP

	Thickener	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA PASTE AP	Inorganic	85	12	-40 to +1200	1	

Synthetic assembly/disassembly paste for food and beverage processing equipment.

Main application: Assembly and disassembly paste with an extremely large range of applications, for example, screw paste for high-alloy steels to optimise the tightening torque, mounting and pressing of bearings, and disks, wheels and bolts, for the lubrication of adjusting mechanisms as well as for drifting, bending, punching, pressing and stamping. Protects from fretting corrosion. Protects from seizing – easy disassembling.





CASSIDA FM RANGE

The FM Series of the CASSIDA product portfolio are white-oil-based or semi-synthetic-based food grade lubricating fluids and greases. They are used in similar applications as the CASSIDA series. Especially in cases of total loss lubrication FM lubricants are preferred – as found for example in the animal feed and beverage industry.

CASSIDA FM Range (semi-synthetic or white-oil-based)

Chain Oils

CASSIDA FM CHAIN OIL 150 | 150 SPRAY | 320 | 320 SPRAY | 460 30

Hydraulic Oils

CASSIDA FM HYDRAULIC OIL 32 | 46 | 68 | 100..... 30

Gear Oils

CASSIDA FM GEAR OIL TLS 150 30

CASSIDA FM GEAR OIL 150 | 220 | 320 | 460 | 680 31

Specialties

CASSIDA FM FLUID DC 20 | 68 31

CASSIDA FM FLUSHING FLUID 32 31

CASSIDA FM HEAT TRANSFER FLUID 32 32

CASSIDA FM SUGAR DISSOLVING FLUID..... 32

CASSIDA FM MACHINE OIL 15 32

FUCHS BIO CLEAN 32

CASSIDA FM FLUID RC 220 33

CASSIDA FM CIRCULATING OIL 220 33

CASSIDA CARTON FREEZER OIL 33

CASSIDA WHITE OIL..... 33

Greases

CASSIDA FM GREASE DC 2 | FM GREASE DC SPRAY 34

CASSIDA FM GREASE EP 1.5 34

CASSIDA FM GREASE AX/EP 0 | 1 | 2 34

CASSIDA FM GREASE AX/EP 0 | 1 | 2 34

CASSIDA FM GREASE HD 1.5 | 2 35


Application Equipment

Grease Gun

HD GREASE GUN CASSIDA 35

CHAIN OILS

CASSIDA FM CHAIN OIL 150 | 150 SPRAY | 320 | 320 SPRAY | 460

	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FM CHAIN OIL 150	150	19	0 to +110 (upper peak: +120)	
CASSIDA FM CHAIN OIL 150 SPRAY	150*	19*	0 to +110 (upper peak: +120)	
CASSIDA FM CHAIN OIL 320	320	34	0 to +110 (upper peak: +120)	
CASSIDA FM CHAIN OIL 320 SPRAY	320*	34*	0 to +110 (upper peak: +120)	
CASSIDA FM CHAIN OIL 460	460	43	0 to +110 (upper peak: +120)	


Chain lubricant for food and beverage processing equipment. Good resistant to fling-off or wash-off. Excellent protection against wear and corrosion.

Main application: Lubrication of drive and conveyer chains and bushes in the food industry. Can be applied by brush or drip feed as well as centralised lubrication system

*after evaporation of solvent

HYDRAULIC OILS

CASSIDA FM HYDRAULIC OIL 32 | 46 | 68 | 100


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FM HYDRAULIC OIL 32	32	5.7	0 to +110 (upper peak: +120)	DIN 51524 HLP
CASSIDA FM HYDRAULIC OIL 46	46	7	0 to +110 (upper peak: +120)	DIN 51524 HLP
CASSIDA FM HYDRAULIC OIL 68	68	9	0 to +110 (upper peak: +120)	DIN 51524 HLP
CASSIDA FM HYDRAULIC OIL 100	100	11.5	0 to +110 (upper peak: +120)	DIN 51524 HLP

Hydraulic fluids for food and beverage processing equipment.

Main application: Hydraulic systems, hydrostatic gears and control systems, plain and anti-friction bearings on food handling and processing equipment.

GEAR OILS

CASSIDA FM GEAR OIL TLS 150


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FM GEAR OIL TLS 150	150	15	0 to +110 (upper peak: +120)	DIN 51517 CLP

Speciality anti-wear gear lubricant specifically designed for use in the food and beverage canning industry. Provides good lubrication even when operating in locations where it is subject to contamination with water, juice and food. Holds these contaminants in suspension, thus protecting metal surfaces from wear and corrosion. Only to be used for total loss systems.

Main application: Suitable for can seamer gearboxes on food handling and processing equipment. May also be used for general machine lubrication.

GEAR OILS

CASSIDA FM GEAR OIL 150 | 220 | 320 | 460 | 680


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FM GEAR OIL 150	220	16.2	0 to +110 (upper peak: +120)	DIN 51517 CLP
CASSIDA FM GEAR OIL 220	220	20	0 to +110 (upper peak: +120)	DIN 51517 CLP
CASSIDA FM GEAR OIL 320	320	27.33	0 to +110 (upper peak: +120)	DIN 51517 CLP
CASSIDA FM GEAR OIL 460	460	30	0 to +110 (upper peak: +120)	DIN 51517 CLP
CASSIDA FM GEAR OIL 680	680	45	0 to +110 (upper peak: +120)	DIN 51517 CLP

Gear lubricants for food and beverage processing equipment.

Main application: Suitable for gearboxes on food handling and processing equipment. May also be used for general machine lubrication or as a flushing fluid.

SPECIALTIES


CASSIDA FM FLUID DC 20 | 68

	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FM FLUID DC 20	22	4	0 to +120 (upper peak: +130)	
CASSIDA FM FLUID DC 68	68	9.5	0 to +120 (upper peak: +130)	

White mineral oil, multipurpose, low-volatility fluids suitable for both direct and incidental food contact applications. Can handle a wide range of applications.

Main application: Absorber oils for edible oil extraction plant solvent recovery systems. Release agent used on grills, loaf pans, cutters, boning benches, chopping blocks or other hard surfaces to help prevent food from adhering during processing. Forming oils for the manufacture of both two- and three-piece cans for food and beverages.

CASSIDA FM FLUSHING FLUID 32


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FM FLUSHING FLUID 32	31	5.2	-10 to +150 (upper peak: +325)	DIN 51522 Q

Specialty cleaning and flushing concentrate for heat transfer systems operating in the food and beverage industry.


Main application: FM FLUSHING FLUID 32 is recommended for use in closed heat transfer systems which suffer from carbon formation due to thermal and oxidative degradation.

SPECIALTIES


CASSIDA FM HEAT TRANSFER FLUID 32

	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FM HTO 32	35	6	0 to +320 (upper peak: +330)	
<p>High-performance heat transfer fluid. Can handle a wide range of application temperatures and has excellent thermal and oxidative stability to minimise cracking and promote long service life.</p>		<p>Main application: For closed-circuit and pressureless heat transfer systems with a bulk oil temperature range of approximately -10°C to max. +320°C where the surface temperature of the heating elements (oil film temperature) should not exceed +330°C.</p>		


CASSIDA FM SUGAR DISSOLVING FLUID

	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FM SUGAR DISSOLVING FLUID	36	5.7	n.a.	
<p>Emulsifiable oil-based cleaning and rust protecting concentrate. Designed to be used in mixtures with potable water on machine surfaces in the food and sugar manufacturing industry.</p>		<p>Main application: For cleaning and flushing sugar or sugar-based deposits from food and beverage manufacturing equipment. For freeing moving parts or screws and bolts that are stuck with sugar deposits. For lubrication of lightly loaded bearings and slideways, especially where sugar deposits are likely to form.</p>		

CASSIDA FM MACHINE OIL 15


	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FM MO 15	22	4	0 to +110 (upper peak: +120)	
CASSIDA FM MO 15 SPRAY	68	9.5	0 to +110 (upper peak: +120)	
<p>Multi-purpose penetrating lubricant and airline lubricant</p>		<p>Main application: FM MACHINE OIL 15 is suitable for use in chains, sprockets, bushes, etc. and as an alternative for Air Line Lubrication systems.</p>		

FUCHS BIO CLEAN

	pH	Density @ 20°C	Activity to Aluminium	Specifications
FUCHS BIO CLEAN	>10	1.08	Passive up to 90°C	NSF Non Food Compound listing A1 (No. 133135)
FUCHS BIO CLEAN PREMIX	12.79	1.04	Passive up to 90°C	NSF Non Food Compound listing A1 (No. 158319)
<p>Solvent free, readily biodegradable, environmentally friendly heavy duty cleaner.</p>		<p>Main application: FUCHS BIO CLEAN is recommended for use in food and pharmaceutical processing facilities</p>		

SPECIALTIES


CASSIDA FM FLUID RC 220

	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FM FLUID RC 220	220	20.4	-10 to +140 (upper peak: +150)	DIN 51517 CLP

Special high-performance fluids specially developed for use in rotary cooking equipment in food and beverage canning plants. Provide good lubrication even when operating in locations where they are subject to contamination with water.

Main application: For use in the centralised systems of rotary cookers and sterilisers which lubricate the can exchange valves and other moving components.


CASSIDA FM CIRCULATING OIL 220

	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA FM CIRCULATING OIL 220	220	19.5		

Specialty circulating oil designed for food and pharma industries.

Main application: FM CIRCULATING OIL 220 is recommended for use in lubricating bearings, gears and chains in circulating systems.


CASSIDA CARTON FREEZER OIL

	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	Specifications
CASSIDA CARTON FREEZER OIL	9.78	2.75		

Fully synthetic lubricant for extreme cold conditions in food processing and canning plants.

Main application: CARTON FREEZER OIL is recommended for use in vane, gear, axial hydraulic pumps and torque sensitive applications exposed to extreme low temperatures.

CASSIDA WHITE OIL




	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Flash Point [°C]	Specifications
CASSIDA WHITE OIL 15	15	0.849	>160	
CASSIDA WHITE OIL 46	46	0.856	>190	
CASSIDA WHITE OIL 68	68	0.864	>200	

White oils of high degree of purity, safe for direct and indirect contact with food

Main application: Recommended for use in general applications that include manufacturing, packing, processing, preparing, treating and packing food. Ideal for applications such as dough and corrugated dividing oil.

GREASES

CASSIDA FM GREASE DC 2 | CASSIDA FM GREASE DC SPRAY



	Thickener	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA FM GREASE DC 2	Inorganic	100	11	-10 to +120	2	
CASSIDA FM GREASE DC 2 SPRAY	Inorganic	100	11	-10 to +120	00*	

White mineral oil grease, multipurpose, suitable for both direct and incidental food contact applications. Can handle a wide range of applications.

Main application: For use as a direct food contact release agent for grills, loaf pans, cutters, boning benches, chopping blocks and other hard surfaces to help prevent food from adhering during processing. Lubrication and protection of seals, guides, bearings and blades operating in food, pharmaceutical and other clean environments where direct food contact is inevitable.

*without propellant


CASSIDA FM GREASE EP 1.5

	Thickener	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA FM GREASE EP 1.5	AICx mod.	200	22	-20 to +130 (upper peak: +140)	1.5	

Modified aluminium complex multipurpose, extreme pressure grease.

Main application: For use on slow to medium Speed plain and rolling element bearings in regular or heavy loaded applications. Recommended for use in machinery requiring frequent changes of the grease charge or with a high product consumption rate, such as machines used to process pet food and animal feed.

CASSIDA FM GREASE AX/EP 0 | 1 | 2


	Thickener	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	NLGI-Grade	Color Code*
CASSIDA FM GREASE AX/EP 0	AICX	180	20	-15 to +121 (upper peak: +129)	0	
CASSIDA FM GREASE AX/EP 1	AICX	180	20	-15 to +121 (upper peak: +129)	1	
CASSIDA FM GREASE AX/EP 2	AICX	180	20	-15 to +121 (upper peak: +129)	2	

High-performance, extreme-pressure aluminium complex greases.

Main application: For use on bearings, bushings and linkages on food; FM GREASE AX/EP NLGI 0 and 1 is recommended enclosed industrial gears and automatic centralised lubrication systems.
FM GREASE AX/EP NLGI 0 ;1 and 2 : Plain and rolling element bearings.
FM GREASE AX/EP NLGI 2: Joints, linkages, slides and a wide range of applications.

GREASES

CASSIDA FM GREASE HD 1.5 | 2

	Thickener	Viscosity at 40°C [mm ² /s]	Viscosity at 100°C [mm ² /s]	Temperature range [°C]	NLGI-Grade	Color Code*
	AICx mod.	550	38	-10 to +140 (upper peak: +150)	1.5	■
	AICx mod.	550	38	-10 to +140 (upper peak: +150)	2	■
Modified aluminium complex heavy-duty, extreme-pressure greases.		Main application: For use on slow to medium-speed plain and rolling element bearings in heavy-loaded and shock-loaded applications. Recommended for use in machinery requiring frequent changes of the grease charge or with a high product consumption rate, such as machines used to process pet food and animal feed.				

Application Equipment

GREASE GUN

HD GREASE GUN CASSIDA

The two-handed gun guarantees clean and safe lubrication of machines in the food industry. It delivers a large volume of lubricant per stroke. Particularly simple handling is achieved with the use of matching cartridges with a screw cap.

The gun is pre-lubricated with food grade grease, which ensures the highest level of food safety.

- Operation pressure up to 400 bar / 5,800 psi
- Ergonomic grips for optimum operation
- Twin-lock system protects the piston from wear and avoids grease escaping the piston
- Protecting cap to prevent contamination at hose end
- Flexible armoured hose for optimum accessibility of lubricating points
- Output: 1.5 cm³/stroke
- Available with 500 g SR cartridges
- Complete discharge of the SR cartridge by special piston shape
- Colour coding of cartridges avoids mixing up different lubricants



The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS in the development and manufacturing of lubricants and represents the current state of the art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS LUBRICANTS application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product range, the products and their manufacturing processes as well as all details of our product information sheets at any time and without warning. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS.

© FUCHS LUBRICANTS All rights reserved.

Innovative lubricants need experienced application engineers

Every lubricant change should be preceded by expert consultation on the application in question. Only then the best lubricant system can be selected. Experienced FUCHS engineers will be glad to advise on products for the application in question and also on our full range of lubricants.



Contact:



FUCHS LUBRICANTS SOUTH AFRICA (Pty) Ltd
A level 1 BEE Contributor
6 Isando road, Isando
1600, Gauteng
Phone : +27 11 565 9600
E-mail : ZA-contact-za@fuchs.com
www.fuchs.com/za/en

The information contained in this product information is based on the experience and expertise of FUCHS LUBRICANTS in the development and manufacturing of lubricants, and represents the current cutting edge. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible. Our products must not be used in aircraft/spacecraft or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product range, the products and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS.